

# SB PACKING HOUSE — EQUIPMENT —

## NICKEL PLATED HYDRAULIC MOTORS



Our PN#	Manufacturer PN#	Displacement
280000	TF0100AS030AAAB-NP	6.1 cu in
280005	TF0130AS030AAAB-NP	7.8 cu in
280006	TF0170AS030AAAB-NP	10.3 cu in
280007	TF0240AS030AAAB-NP	14.5 cu in
280008	TF0280AS030AAAB-NP	17.1 cu in
280009	TF00475AS030AAAB-NP	29.1 cu in
280010	TG00625AS030AAAB-NP	38.0 cu in
280011	TG0960AS030AAAB-NP	58.5 cu in

- All motors supplied with #10 SAE O ring Ports Nickel Plating is Standard
- 3.25" Pilot Mount (SAE A)
- 1-1/4 Keyed Shaft
- Excellent for Low Speed High Torque Applications

**OTHER CONFIGURATIONS AVAILABLE**

**Conveyor Motor Sizing Worksheet**

Length of Conveyor in Feet \_\_\_\_\_

Width of Conveyor in inches \_\_\_\_\_

Product weight per foot (15 lbs per foot or 25 lbs per foot) \_\_\_\_\_

Belt style (i.e. Intralox 800 series) \_\_\_\_\_

Hydraulic Pressure Available \_\_\_\_\_

Hydraulic Flow Requirement \_\_\_\_\_

Service Factor Required (1.5 SF is Standard) \_\_\_\_\_

Conveyor Speed in Feet Per Second \_\_\_\_\_

Sprocket Size \_\_\_\_\_